

# Содержание

Пример конфигурации интерфейсов .....	3
---------------------------------------	---



# Пример конфигурации интерфейсов

```
fast-epdg {
  swu {
    <config-name> {
      apn=
      ike=aes256-sha256-sha1-prfsha256-prfsha1-modp2048-modp1024!
      esp=aes256-sha256-sha1-modp2048-modp1024!
      leftauth=eap
      leftsubnet=
      rightauth=eap-diameter
      rightsourceip=%epdg
    }
  }
}

auth {
  interface =
  accounting =
  swm {
    app_id = swm
    realm =
    host =
    vendor_id =
    <server-name> {
      priority =
      local =
      remote =
      proto =
    }
  }
}

swx {
  app_id = swx
  realm =
  host =
  vendor_id =
  <server-name> {
    priority =
    local =
    remote =
    proto =
  }
}

s6b {
  app_id = s6b
  realm =
  host =
  vendor_id =
  <server-name> {
    priority =
```

```

        local =
        remote =
        proto =
    }
}

tunnel {
    iface =
    pdn =
    pgw {
        gtp {
            mcc =
            mnc =
            tac =
            cid =
            enbid =
            realm =
            <server-name> {
                apn =
                priority =
                devname =
                devmode =
                subnet =
                qos {
                    qci =
                    mbr_ul =
                    mbr_dl =
                    gbr_ul =
                    gbr_dl =
                }
                gtp-c {
                    local =
                    remote =
                }
                gtp-u {
                    local =
                    remote =
                }
            }
        }
    }
}

syslog {
    daemon {
        ike =
        cfg =
        lib =
    }
}

```

