

Содержание

Пример конфигурации интерфейсов	3
--	-------	---

Пример конфигурации интерфейсов

```
fast-epdg {
    swu {
        <config-name> {
            apn=
                ike=aes256-sha256-sha1-prfsha256-prfsha1-modp2048-modp1024!
                esp=aes256-sha256-sha1-modp2048-modp1024!
            leftauth=eap
            leftsubnet=
            rightauth=eap-diameter
            rightsourceip=%epdg
        }
    }

    auth {
        interface =
        accounting =
        swm {
            app_id = swm
            realm =
            host =
            vendor_id =
            <server-name> {
                priority =
                local =
                remote =
                proto =
            }
        }
        swx {
            app_id = swx
            realm =
            host =
            vendor_id =
            <server-name> {
                priority =
                local =
                remote =
                proto =
            }
        }
    }

    s6b {
        app_id = s6b
        realm =
        host =
        vendor_id =
        <server-name> {
            priority =
        }
    }
}
```

```
        local =
        remote =
        proto =
    }
}

tunnel {
    iface =
    pdn =
pgw {
    gtp {
        mcc =
        mnc =
        tac =
        cid =
        enbid =
        realm =
        <server-name> {
            apn =
            priority =
            devname =
            devmode =
            subnet =
            qos {
                qci =
                mbr_ul =
                mbr_dl =
                gbr_ul =
                gbr_dl =
            }
        }
        gtp-c {
            local =
            remote =
        }
        gtp-u {
            local =
            remote =
        }
    }
}
}

syslog {
    daemon {
        ike =
        cfg =
        lib =
    }
}
```

}