

Содержание

- Identification of L2 and L3 subscribers 3
 - L3-subscribers* 3
 - Radius Authorization 4
 - L2-subscribers* 4

Identification of L2 and L3 subscribers

L3-subscribers

FastDPI 12 introduces support for identifying L2 subscribers by VLAN/Q-in-Q.

Previously, the way of subscriber identification was only his MAC-address, which could lead to problems if two different subscribers belonging to different VLANs, have the same MAC-address.

FastDPI 12 introduces a new `fastdpi.conf` setting: `bras_subs_id`, which is a type of L2 subscriber identification. It specifies a list, in order of preference, of what to consider to be the L2-subscriber ID.

Valid values in the list:

- `mac` - The subscriber's MAC address (srcMAC of the packet from the subscriber) is the subscriber's identifier. This type is applicable to any network, including VLAN and Q-in-Q (VLANs are not counted).
- `vlan+mac` - the subscriber identifier is the VLAN + subscriber's MAC. This type applies only to VLANs, but does not apply for Q-in-Q.
- `qinq` - the subscriber identifier is Q-in-Q. Applicable for Q-in-Q networks only.
- `qinq+mac` - subscriber identifier is Q-in-Q + subscriber's MAC. Applicable for Q-in-Q networks only.

The default value is `bras_subs_id=mac` (for compatibility with previous versions)

Setup example:

```
bras_subs_id=qinq+mac,vlan+mac,mac
```

is interpreted as follows:

- If the packet is Q-in-Q - then the identifier is Q-in-Q + subscriber's MAC,
- otherwise if the package is VLAN - then the identifier is VLAN + subscriber's MAC,
- otherwise the identifier is the subscriber's MAC.

Instead of a list you can set it to `auto`:

```
bras_subs_id=auto
```

which is equal to:

```
bras_subs_id=qinq+mac,vlan+mac,mac
```

We recommend to use the `auto` value for `bras_subs_id`.

If no identification type is defined for an incoming packet, then such subscriber is not terminated, all packets of the subscriber are dropped. This is possible for the following example:

```
bras_subs_id=qinq+mac
```

when the incoming packet from the subscriber is not Q-in-Q.

Radius Authorization

In the Radius L2 authorization request, the subscriber ID is passed in the VSA attribute VasExperts-L2-SubsId as a string:

ATTRIBUTE	VasExperts-L2-SubsId	14	string
-----------	----------------------	----	--------

The format of the string representation of the identifiers is as follows:

- mac: "[1]xx:xx:xx:xx:xx:xx", xx - subscriber's MAC address, e.g.: [1]02:42:89:33:7b:3e - subscriber MAC=02:42:89:33:7b:3e
- vlan+mac: "[2]N/xx:xx:xx:xx:xx:xx", N - VLAN number, e.g., [2]56/02:42:89:33:7b:3e - subscriber MAC=02:42:89:33:7b:3e в VLAN=56
- qinq: "[3]N.N", N - VLAN numbers, e.g.: [3]56.234 - subscriber in Q-in-Q=56.234
- qinq+mac: "[4]N.N/xx:xx:xx:xx:xx:xx", e.g.: [4]56.234/02:42:89:33:7b:3e - subscriber MAC=02:42:89:33:7b:3e в Q-in-Q=56.234

If the subscriber's L2 identifier is unknown, then VasExperts-L2-SubsId=[0]<n/a>.

L2-subscribers