

Table of Contents

kea_cfg_opt15	3
----------------------------	---

kea_cfg_opt15

Example of configuration for option 15 (dhcp6_poolname_opt=1) for Kea DHCPv6:

```
# Class Description
"client-classes": [
  { # opt15 User-Class
    "name": "ppp_userclass_ip6_pool",
    "test": "substring( option[15].hex, 2, 100 ) ==
'ppp_userclass_ip6_pool'",
    # In option-data you can set options common to this class
    "option-data": [
      {
        "name": "dns-servers",
        "space": "dhcp6",
        "data": "2001:db8:2::dead:cafe, 2001:db8:2::cafe:dead"
      }
    ]
  },
  # Description of other classes
  # ...
] # end of client-classes

# Setting pools
"shared-networks": [
  {
    "name": "MyNetworks",

    # The pools are accessed on behalf of the relay
    "relay": {
      "ip-addresses": ["2001::1"]
    },

    "subnet6": [
      {
        "client-class": "ppp_userclass_ip6_pool",
        "subnet": "2a02:400:1::/48",

        # IMPORTANT! Only a PD prefix with a length one less than the
value of the
        # of the ipv6_subnetmask parameter in fastdpi.conf (default
value is 64).
        # SCAT itself splits this prefix into 2 ipv6_subnetmask lengths:
the younger one
        # /64 subnet is given to the client, the older one is under the
client prefix
        "pd-pools": [
          {
            "prefix": "2a02:400:1::",
```

```
        "prefix-len":48,  
        "delegated-len": 63  
    }  
    ]  
}  
  
    # description of other pools  
    # ...  
] # end of subnet6  
] # end of shared-networks
```