

Содержание

kea_cfg_opt17	3
----------------------------	----------

kea_cfg_opt17

Example of configuration for option 17 (dhcp6_poolname_opt=2) for Kea DHCPv6:

```
# Pool Description
"client-classes": [
    {
        "name": "test-ipv6-pool",
        "test": "vendor[43823].option[1].hex == 'test-ipv6-pool'",
            # In option-data you can set options common to this class
        "option-data": [
            {
                "name": "dns-servers",
                "space": "dhcp6",
                "data": "2001:db8:2::dead:beef, 2001:db8:2::cafe:babe"
            }
        ],
        # Description of other classes
        # ...
    } # end of client-classes

# Setting pools
"shared-networks": [
    {
        "name": "MyNetworks",

        # The pools are accessed on behalf of the relay
        "relay": {
            "ip-addresses": ["2001::1"]
        },

        "subnet6": [
            # test-ipv6-pool
            {
                "client-class": "test-ipv6-pool",
                "subnet": "2a02:100:1::/48",

                    # IMPORTANT! Only a PD prefix with a length one less than the
                    value of the
                    # of the ipv6_subnetmask parameter in fastdpi.conf (default
                    value is 64).
                    # SSG itself splits this prefix into 2 ipv6_subnetmask lengths:
                    the younger one
                    # /64 subnet is given to the client, the older one is under the
                    client prefix
                "pd-pools": [
                    {
                        "prefix": "2a02:100:1::",

```

```
        "prefix-len":48,
        "delegated-len": 63
    }
],
# description of other pools
#
] # end of subnet6
] # end of shared-networks
```