

Содержание

RADIUS attributes	3
--------------------------------	----------

RADIUS attributes

FastPCRF passes the following attributes within the Accounting-Request:

VasExperts-L2-SubsId - L2-subscriber ID.

Framed-IP-Address - (for the IPv4 only) is the subscriber IPv4 address; in case of NAT 1:1, this attribute value can be [configured](#).

Framed-IPv6-Prefix - (for the IPv6 only) IPv6 subscriber subnet prefix.

Framed-IPv6-Address - (for the IPv6 only) IPv6 subscriber address. Only high bits of the IP address are most significant, as specified by the IPv6 prefix. For example, for the prefix 2001:1::/64, the value of this attribute is 2001:1::.

Acct-Session-Id - RADIUS accounting session identifier.

Acct-Status-Type - the request type:

- [1] start - beginning of the accounting session. Statistics are not transmitted within this request, the only session id is transferred;
- [2] stop - termination of the accounting session. This request contains the final session statistics;
- [3] interim-update - interim statistics.

Acct-Delay-Time - is the timeout in seconds between receiving the last billing netflow statistics from the fastdpi and sending this Accounting-Request. In fact, this is a measure of data "obsolescence".

Class - if during authorization the Access-Accept/Access-Reject contains the Class attribute, then it will be transferred in all the accounting requests.

NAS-Port-Type, NAS-Port, NAS-IP-Address, NAS-Identifier - are formed similarly to the [Access-Request](#).

Statistics (accounting data) are defined in the [RFC-2866](#) and are passed only for Acct-Status-Type= 2 or 3:

- Acct-Input-Packets - the number of packets sent to the subscriber (inet → subs direction)
- Acct-Output-Packets - number of packets from the subscriber (subs → inet direction)
- Acct-Input-Octets - number of bytes sent to the subscriber (inet → subs direction)
- Acct-Output-Octets - number of bytes from the subscriber (subs → inet direction)
- Acct-Input-Gigawords ([RFC-2869](#))
- Acct-Output-Gigawords ([RFC-2869](#))

in addition, statistics on the cs0-cs7 [traffic classes](#) are transmitted in vendor-specific-attributes (VSA). The following VSAs are defined for the vendor-id=43823:

ATTRIBUTE	VasExperts-Acct-Traffic-Class-Name	16	string
ATTRIBUTE	VasExperts-Acct-Traffic-Class-Input-Octets	17	integer64
ATTRIBUTE	VasExperts-Acct-Traffic-Class-Output-Octets	18	integer64

```
ATTRIBUTE VasExperts-Acct-Traffic-Class-Input-Packets 19 integer64
ATTRIBUTE VasExperts-Acct-Traffic-Class-Output-Packets 20 integer64
```

here the VasExperts-Acct-Traffic-Class-Name is the traffic class name, "cs0", "cs1", ..., "cs7", the rest attributes contain statistics for this traffic class. Below is the example of the packet (only the first two traffic statistics are unfolded):

```
Frame 211: 576 bytes on wire (4608 bits), 576 bytes captured (4608 bits)
Ethernet II, ...
Internet Protocol Version 4, ...
User Datagram Protocol, Src Port: 41754, Dst Port: 1815
RADIUS Protocol
  Code: Accounting-Request (4)
  Packet identifier: 0xfc (252)
  Length: 534
  Authenticator: 02495762cbcef01d257fa82eb8f320b3
  [The response to this request is in frame 233]
  Attribute Value Pairs
    AVP: l=6 t=NAS-Port-Type(61): Virtual(5)
    AVP: l=6 t=NAS-Port(5): 0
    AVP: l=10 t=NAS-Identifier(32): FastPCRF
    AVP: l=6 t=Framed-IP-Address(8): 192.168.0.52
    AVP: l=6 t=Service-Type(6): Framed(2)
    AVP: l=18 t=Acct-Session-Id(44): 3400a8c0311fae6b
    AVP: l=6 t=Acct-Authentic(45): RADIUS(1)
    AVP: l=6 t=Acct-Status-Type(40): Interim-Update(3)
    AVP: l=6 t=Acct-Delay-Time(41): 6
    AVP: l=6 t=Acct-Input-Packets(47): 0
    AVP: l=6 t=Acct-Output-Packets(48): 1956
    AVP: l=6 t=Acct-Input-Octets(42): 0
    AVP: l=6 t=Acct-Input-Gigawords(52): 0
    AVP: l=6 t=Acct-Output-Octets(43): 2173116
    AVP: l=6 t=Acct-Output-Gigawords(53): 0
    AVP: l=51 t=Vendor-Specific(26) v=VAS Experts(43823)
      AVP Type: 26
      AVP Length: 51
      VSA: l=5 t=VasExperts-Acct-Traffic-Class-Name(16): cs0
      VSA: l=10 t=VasExperts-Acct-Traffic-Class-Input-Octets(17):
0000000000000000
      VSA: l=10 t=VasExperts-Acct-Traffic-Class-Output-Octets(18):
000000000002128bc
      VSA: l=10 t=VasExperts-Acct-Traffic-Class-Input-Packets(19):
0000000000000000
      VSA: l=10 t=VasExperts-Acct-Traffic-Class-Output-Packets(20):
00000000000007a4
    AVP: l=51 t=Vendor-Specific(26) v=VAS Experts(43823)
      AVP Type: 26
      AVP Length: 51
      VSA: l=5 t=VasExperts-Acct-Traffic-Class-Name(16): cs1
      VSA: l=10 t=VasExperts-Acct-Traffic-Class-Input-Octets(17):
0000000000000000
```

