

Table of Contents

| | |
|--|---|
| Update guide | 3 |
| <i>Preparation for update</i> | 3 |
| <i>Special operating conditions</i> | 3 |
| <i>DPI update</i> | 3 |
| <i>Service restart</i> | 4 |
| <i>Operating system update</i> | 4 |
| <i>Version rollback</i> | 4 |
| <i>Important notes</i> | 5 |

Update guide



Starting from version [12.0](#), DPI is supported **only** on centos 8.x and [veos](#).

Preparation for update

- Make sure that the DPI configuration and dependent services (pcrf, radius) are valid.
- Check the currently installed version:

```
yum info fastdpi
```

- If centos 8.x is used, **once** switch repositories to vault:

```
sed -i -e '/^mirrorlist=http:\\\\//d' -e 's/^#  
*baseurl=http:\\\\mirror.centos.org/baseurl=http:\\\\vault.centos.org/'  
/etc/yum.repos.d/CentOS-*.repo
```

- If there are dependency issues or the update cannot be found, run:

```
yum clean all
```

Special operating conditions

For virtual machines, old processors (approximately before 2009), and old amd processors (before ryzen):

Before updating, run:

```
touch /etc/dpi/noprioadj
```

In this case, DPI will start with a normal (non-realtime) priority, which reduces cpu (sys) load but may slightly increase latency.

DPI update

- Main version update:

```
yum update fastdpi
```

- Installation of a test (beta) version:

```
yum --enablerepo vasexperts-beta update fastdpi
```



If the module `yaml` error occurs during update, update the module:

```
dnf upgrade libmodulemd
```

Service restart

After updating or changing the version, **be sure** to restart DPI:

```
service fastdpi restart
```

If PCRF and/or radius are used, they must also be restarted (only with a valid configuration):

```
service fastpcrf restart  
service fdpi_radius restart
```

Recommended pcrf restart order:

```
service fastdpi stop  
service fastpcrf restart  
service fastdpi start
```

Operating system update



Do not update the linux kernel version and kernel-dependent utilities.

- For centos 8.x:

```
yum update
```

Version rollback

- Example rollback to version 14.0:

```
yum downgrade fastdpi-14.0 fastpcrf-14.0 dpiutils-14.0 fastradius-14.0
```

- Example rollback to version 12.4:

```
yum downgrade fastdpi-12.4-0 fastpcrf-12.4-0
```

After rollback, service restart is required:

```
service fastdpi restart
```

Important notes

- Customers using bras functionality must take changes into account when upgrading to new versions.
- Updating the linux kernel may break binary compatibility with kernel abi and cause issues with network driver loading.
- If the kernel was updated, temporarily configure booting the previous version via grub by setting the required default parameter value in the `/etc/grub.conf` file.