


Table of Contents

Backups	3
Configuration	3
<i>Enable DB backup</i>	3
<i>Enable FS backup</i>	4
<i>Remote server for storing backups settings</i>	4
<i>Saving changes</i>	5
Data recovery	5
<i>Restoring DB from backup</i>	6
<i>Restoring FS from backup</i>	6

Backups

Starting with version 2.25.9, the function of backup DB and FS has appeared. By enabling the function, you can configure the frequency of copying, storage duration, as well as export via SCP to a remote storage.


Move to the DB and FS settings section, open the Administrator menu item, section «**Backup settings**».



Configuration

Enable DB backup

To enable DB backup, select "**Enabled**".



Specify the following settings

- **BACKUP_DB_ENABLED** - enable DB backup. (Default value is Disabled)
- **BACKUP_DB_INTERVAL_MINUTES** - backup DB time interval, minutes. (Default value is 1440)
- **BACKUP_DB_PATH** - backup DB save path. (Default path is /var/dpiui2_backup/db)
- **BACKUP_DB_DELETE_OLD_INTERVAL_MINUTES** - delete old DB backups interval, minutes. (Default value is 0)



When set to "0", old backups will not be deleted.

Enable FS backup



FS backup include **.env** files and folder contents **/var/dpiui2/backend/storage**

To enable FS backup, select "**Enabled**".

Specify the following settings

- **BACKUP_FS_ENABLED** - enable FS backup. (Default value is Disabled)
- **BACKUP_FS_INTERVAL_MINUTES** - backup FS time interval, minutes. (Default value is 1440)
- **BACKUP_FS_PATH** - backup FS save path. (Default path is /var/dpiui2_backup/fs)
- **BACKUP_FS_DELETE_OLD_INTERVAL_MINUTES** - delete old FS backups interval, minutes. (Default value is 0)



When set to "0", old backups will not be deleted.

Remote server for storing backups settings

- **BACKUP_SCP_HOST** - remote server host for storing backups.
- **BACKUP_SCP_PORT** - remote server port for storing backups.
- **BACKUP_SCP_USER** - backup storage username.

- **BACKUP_SCP_PASSWORD** - backup storage password.



SCP will use key authentication if no password is specified.

- **BACKUP_SCP_DB_PATH** - backup DB remote path. (Default path is /var/dpiui2_backup/db)



The folder must exist. The user must have access rights to this folder.

- **BACKUP_SCP_FS_PATH** - backup FS remote path. (Default path is /var/dpiui2_backup/fs)



The folder must exist. The user must have access rights to this folder.

Saving changes

To save the edited parameters, click the "**Save**" button.

The screenshot shows the VAS Experts GUI configuration page. On the left is a sidebar with a search bar and a list of categories: SSG control, PCRF control, QoS analytics, VAS cloud services, Lawful interception, Classifier, Administrator, Equipment, Users, Roles, GUI configuration (selected), GUI logs, GUI update, QoS Stor configuration, QoS Stor logs, and Hardware SSH terminal. The main area is titled 'Administrator > GUI configuration'. It contains a 'Settings' section with a 'Save' button highlighted by a green arrow. Below 'Settings' are several sub-sections: Common, Jobs intervals and periods, QoS Stor: DB (Clickhouse) connection, QoS Stor: DB lifetime settings, QoS Stor: Discs settings, SMTP settings, System, DB (MySQL) connection, Uir settings, Push notifications settings, Lawful interception, SSO authorization settings, Maps settings, VASCloud settings, Cluster settings, Backup settings (selected), and Backup auto restoration settings. The 'Backup settings' section is expanded, showing a list of configuration items with their current values and a dropdown menu to toggle them on or off. The items are: Enable DB backup (BACKUP_DB_ENABLED) - Disabled; Backup DB time interval, minutes (BACKUP_DB_INTERVAL_MINUTES) - 2; Backup DB save path (BACKUP_DB_PATH) - /var/dpiui2_backup/db; Delete old DB backups interval, minutes (BACKUP_DB_DELETE_OLD_INTERVAL_MINUTES) - 0; Enable FS backup (BACKUP_FS_ENABLED) - Disabled; Backup FS time interval, minutes (BACKUP_FS_INTERVAL_MINUTES) - 2; Backup FS save path (BACKUP_FS_PATH) - /var/dpiui2_backup/fs; Delete old FS backups interval, minutes (BACKUP_FS_DELETE_OLD_INTERVAL_MINUTES) - 0; Remote server host for storing backups (BACKUP_SCP_HOST) - 192.168.1.97; Remote server port for storing backups (BACKUP_SCP_PORT) - 22; Backup storage username (BACKUP_SCP_USER) - root; and Backup storage password (BACKUP_SCP_PASSWORD) - (empty).

Data recovery

To restore data from Backup, make sure that the dpiui2 server is [installed and running](#).

Restoring DB from backup

To restore the database, upload the database backup file to the dpiui2 server and run the following command in the terminal:

```
sh /var/www/html/dpiui2/backend/app_bash/vas_codebase/restore_backup_db.sh  
dpiui2 dpiui2_db_backup.X.tar.gz
```

Restoring FS from backup



The file backup includes the **.env** file and **/var/dpiui2/backend/storage** directory contents.

To restore the dpiui2 FS upload the backup file to the dpiui2 server and run the following command:

```
sh /var/www/html/dpiui2/backend/app_bash/vas_codebase/restore_backup_fs.sh  
dpiui2 dpiui2_fs_backup.X.tar.gz
```



After restoring the database and files, make sure everything works.