

Table of Contents

- Changelog of SSG BETA-version** 3
 - Changes in version 14.0 BETA1 3
 - Changes in version 14.0 BETA2 3
 - Changes in version 14.0 BETA3 4
 - Changes in version 14.0 BETA4 4
 - Changes in version 14.0 BETA4.1 5
 - Changes in version 14.0 BETA4.2 5
 - Update instructions 5

Changelog of SSG BETA-version

Changes in version 14.0 BETA1

1. [BRAS] Support for L2TP termination
2. [BRAS] Support for DHCP-Dual
3. [DPI] Migration to DPDK 24.11, support for new NICs (Intel E830 200G, Intel E630, Napatech SmartNIC)
4. [CLI] Added support for subs_id in commands: dhcp show, dhcp reauth, dhcp6 show, dhcp6 reauth, and dhcp disconnect

Changes in version 14.0 BETA2

1. [DPI] New protocols added: AGORA_STREAMS(49314), AZAR_CALL(49315), WECHAT_CALL(49316), TEAMS_CALL(49317). [List of protocols](#)
2. [DPI] Improved support for LINE_CALL, VYKE_CALL protocols. [List of protocols](#)
3. [DPI] Fixed smartdrop behavior
4. [DPI] Added validation for complex protocols. [List of protocols](#)
5. [DPDK] Increased the maximum number of dispatchers to 32
6. [IPFIX/Netflow] Added the ability to change IPFIX/Netflow parameters without restarting fastDPI. A new config parameter ipfix_reserved has been added to reserve memory for enabling/changing IPFIX/Netflow parameters. If IPFIX/Netflow parameters are set in the configuration file, memory reservation for IPFIX/Netflow is automatically enabled and parameters/new exporter types can be changed without restarting fastDPI.
7. [FastRadius] It is now possible to set both bind_ipv6_address and bind_ipv6_subnet. If the Framed-IPv6-Prefix has a /128 mask, it is not checked against the bind_ipv6_subnet restriction.
8. CLI command dev info now includes the name of the LAG that the port belongs to
9. [PCRF][PPP][Framed-pool] Added: DHCP option Client-Id now includes tunnel-IP as part of the subscriber ID. Format of DHCP option Client-Id with fastpcrf.conf option dhcp_client_id=1 is as follows:

```
[conntype][subs_id][tunnel_ip]
```

```
conntype = 1 (1 byte)
subs_id   - 16 bytes
tunnel_ip - 4 bytes
```

Tunnel IP is available in L2TP; for PPPoE, tunnel IP = 0.

10. [IPFIX] Message aggregation added for IPFIX streams: FullFlow/DNS/META/NAT
11. [IPFIX] Added parameter ipfix_mtu_limit to restrict maximum message size for IPFIX UDP packets
12. [IPFIX DNS] New elements added to IPFIX DNS: 224 (ipTotalLength) and 43823:3206 (DNS transaction id)
13. [VRRP] Fixed proper handling of the vrrp_enable option change
14. [BRAS][PPP] PPP session key is now compound: l2subs_id + tunnel-IP. For PPPoE sessions, tunnel IP = 0. CLI commands that use subs_id as a key (subs prop show, l2tp show

session, l2tp term, etc.) may now return multiple entries with the same l2subs_id.

Changes in version 14.0 BETA3

1. [DPI] Added cloud protocols with identifiers 55296..58367
2. [IPFIX] Fixed IPFIX exporter reinitialization bugs
3. [BRAS][subs_grooming] Fixed potential crash due to race condition during fastDPI shutdown
4. [CLI] Added commands to display mempool properties and statistics

```
hal mempool props
hal mempool stat
```

DPDK must be built with statistics collection enabled to display mempool stats

5. [BRAS][DHCP] Fixed crash when parsing Framed-Pool Renew response if it contains no DHCP options
6. [PCRF][Acct] Fixed: Interim-Update sending is now disabled when Acct-Interim-Interval = 0 is explicitly set in the RADIUS response
7. [VASE_CLI] Created a unified CLI for managing DPI, BRAS, DHCP (KEA), ROUTER (BIRD) with support for authorization and command logging via TACACS (VEOS 8.x required)
8. [SNMP] Created a module for monitoring system components via SNMP

Changes in version 14.0 BETA4

1. [DPI] Added DOQ 49318 protocol (DNS-over-QUIC)
2. [Router] Announcing subscriber white addresses for 1:1 NAT individually and after authentication
3. [PCRF] Added support for service 19 "DNS spoofing", profile required.
4. [DPDK] Added dpdk_engine=6 (mqr-x-bridge) — number of RSS dispatchers per bridge. Total number of dispatchers = dpdk_rss * number of bridges. NIC configuration: RX queue count = dpdk_rss, TX queue count = number of worker threads (num_threads). Intended for setups with many bridges (dev1:dev2:dev3:...) for 100G+ NICs, as a replacement for the cluster approach. On-stick devices are supported.
5. [DPDK] Removed dedicated mempools. The fastdpi.conf option dpdk_emit_mempool_size is deprecated and no longer used.
6. [VLAN-Rule] Moved vlan group data from UDR to SDR. Global rules for vlan drop/pass/hide/permit set by the previous CLI command vlan group were converted and moved from UDR to SDR, with removal from UDR.
7. [VLAN] VLAN rules — added CLI commands:
 1. vlan rule add - add new rule to SDR
 2. vlan rule modify - modify existing rule in SDR
 3. vlan rule delete - delete rule from SDR
 4. vlan rule show - show all rules for the specified VLAN/QinQ
 5. vlan rule dump - dump all rules in SDR
 6. vlan rule purge vlan/qinq/all - clear SDR for VLAN/QinQ or both
 7. vlan rule apply - apply rules; by default, rules are applied 5 minutes after the last SDR modification
8. [IPv6] Added direction detection in combined traffic (IN+OUT on one port) based on the local flag for IP addresses. Enabled via combined_io_direction_mode option

Changes in version 14.0 BETA4.1

1. [BRAS] Fixed compatibility with the old format of service 18, where there were fewer protocols and both fields in the profile needed to be filled
2. [DPI] Lowered detection priority for telegram_tls

Changes in version 14.0 BETA4.2

1. [DPI] Improved detection of WECHAT and WECHAT_CALL
2. [BRAS][Framed-Route] Fixed: possible crash when freeing memory
3. [BRAS] Refactored PCRF connectivity: in the new implementation, all connections are equal; an error on any triggers reconnection of all connections and a switch to another PCRF. Added CLI commands:
 1. `pcrf connect show` — show current status and accumulated statistics for PCRF connections.
 2. Force connection to the specified PCRF `pcrf connect switch [<pcrf_index>]`, where `<pcrf_index>` is the index of the connection line in the `auth_server` parameter. If `<pcrf_index>` is not specified — defaults to 0.
4. [IPFIX DNS] Added the ability to send DNS MX responses via IPFIX. Enabled by setting bit 3 (4) of the `ajb_save_dns` parameter

Update instructions

You can check the current installed version with the command below

```
yum info fastdpi
```

If you have CentOS 6.x or CentOS 8.x installed, then switch the repository once with the command:

```
sed -i -e '/^mirrorlist=http:\/\/\/d' -e 's/^#  
*baseurl=http:\/\/mirror.centos.org/baseurl=http:\/\/vault .centos.org/'  
/etc/yum.repos.d/CentOS-*.repo
```

and then update as usual.

To install the test version, you should issue the following command:

```
yum --enablerepo vasexperts-beta update fastdpi
```

Downgrade to 13.3:

```
yum downgrade fastdpi-13.3 fastpcrf-13.3 dpiutils-13.3 fastradius-13.3
```



After an update or version change, a restart of the service is required.