

# Table of Contents

Remote execution of SSH commands ..... 3



# Remote execution of SSH commands

We advise to authenticate users by public keys to execute command on DPI server remotely by SSH with no need to enter password.

To use this method: on the control server:

1. We create a pair of public and private keys:

```
ssh-keygen -t rsa
```

We select default values in a functionality of ssh-agent to store passwords.))

2. We keep the secret phrase empty to simplify further usage((Alternatively, one can use the funcNext, we copy the public key to DPI server:

```
ssh-copy-id dpi_user@dpi_host  
or manually:  
cat ~/.ssh/id_rsa.pub | ssh dpi_user@dpi_host "mkdir -p ~/.ssh && cat  
>> ~/.ssh/authorized_keys"
```

Then we check and fix the rights on file authorized\_keys on DPI server:

```
chmod 700 ~dpi_user/.ssh/  
chmod 600 ~dpi_user/.ssh/authorized_keys  
restorecon -Rv ~dpi_user/.ssh/
```

Next, we check the operation of the remote execution of fdpi\_ctrl from the control server:

```
ssh dpi_user@dpi_host "fdpi_ctrl load --service 6 --login test"
```

In case this instruction does not work, try to find some hints in the log file /var/log/secure on DPI server. One can also switch the diagnostic mode on SSH: ssh -v ...