

Содержание

5 Information on command result 3

5 Information on command result

For all parameters except of list

Result processing ... a/b/c/d/e

The symbolic names are indicated in parenthesis:

- a - total records
- b - records successfully processed
- c - some server's error occurred
- d - the attribute(s) was set already
- e - the attribute was not set (meaningful on removal)

Example (the first run):

```
fdpi_ctrl load --service 1,2,3 --cidr 192.168.0.0/19
Autodetected fastdpi params : dev='lo', port=29001
connecting 127.0.0.1:29001 ...
-----
Result processing CIDR=192.168.0.0/19 : 8192/8192/0/0/0
```

Example (the second run: the attribute already set):

```
fdpi_ctrl load --service 1,2,3 --cidr 192.168.0.0/19
Autodetected fastdpi params : dev='lo', port=29001
connecting 127.0.0.1:29001 ...
-----
Result processing CIDR=192.168.0.0/19 : 8192/0/0/8192/0
```

For 'list' parameter

Result processing ... a/b/c

The symbolic names are indicated in parenthesis:

- a - total records
- b - the attribute was set (in this case it is a service)
- c - the attribute was not set

Example:

```
fdpi_ctrl list --service --cidr 192.168.0.0/19
A lot of output lines. The last lines are:
192.168.31.249 1,2,3 (0x7)
192.168.31.250 1,2,3 (0x7)
192.168.31.251 1,2,3 (0x7)
192.168.31.252 1,2,3 (0x7)
192.168.31.253 1,2,3 (0x7)
192.168.31.254 1,2,3 (0x7)
192.168.31.255 1,2,3 (0x7)
```

Result processing CIDR=192.168.0.0/19 : 8192/8192/0