

Содержание

5 Information on command result 3

5 Information on command result

For all parameters except of list

Result processing ... a/b/c/d/e

The symbolic names are indicated in parenthesis:

- a - total records
- b - records successfully processed
- c - some server's error occurred
- d - the attribute(s) was set already
- e - the attribute was not set (meaningful on removal)

Example (the first run):

```
fdpi_ctrl load --service 1,2,3 --cidr 192.168.0.0/19
Autodetected fastdpi params : dev='lo', port=29001
connecting 127.0.0.1:29001 ...
-----
Result processing CIDR=192.168.0.0/19 : 8192/8192/0/0/0
```

Example (the second run: the attribute already set):

```
fdpi_ctrl load --service 1,2,3 --cidr 192.168.0.0/19
Autodetected fastdpi params : dev='lo', port=29001
connecting 127.0.0.1:29001 ...
-----
Result processing CIDR=192.168.0.0/19 : 8192/0/0/8192/0
```

For 'list' parameter

Result processing ... a/b/c

The symbolic names are indicated in parenthesis:

- a - total records
- b - the attribute was set (in this case it is a service)
- c - the attribute was not set

Example:

```
fdpi_ctrl list --service --cidr 192.168.0.0/19
A lot of output lines. The last lines are:
192.168.31.249 1,2,3 (0x7)
192.168.31.250 1,2,3 (0x7)
192.168.31.251 1,2,3 (0x7)
192.168.31.252 1,2,3 (0x7)
192.168.31.253 1,2,3 (0x7)
192.168.31.254 1,2,3 (0x7)
192.168.31.255 1,2,3 (0x7)
```

Result processing CIDR=192.168.0.0/19 : 8192/8192/0

For 'profile' parameter

Profile creation

Result processing ... a/b/c/d

Symbolic notations are given in parentheses:
a - in total
b - succeeded
c - internal error (look through fastdpi_alert.log)
d - profile already exists (in this case there is a41 profile with
corresponding characteristics for the service 4)

Example (the first run):

```
fdpi_ctrl load profile --service 4 --profile.name a41 --profile.json '{
"url_list" : "http://mysite.ru/myfile.bin" , "redirect" :
"http://mysite.ru/block", "federal" : true }'
Autodetected fastdpi params : dev='em1', port=29000
connecting 5.200.43.18:29000 ...
=====
-----
1/1/0/0
```

Example (the second run):

```
fdpi_ctrl load profile --service 4 --profile.name a41 --profile.json '{
"url_list" : "http://mysite.ru/myfile.bin" , "redirect" :
"http://mysite.ru/block", "federal" : true }'
Autodetected fastdpi params : dev='em1', port=29000
connecting 5.200.43.18:29000 ...
=====
-----
1/0/0/1
```

Example (if a profile can not be specified for the service):

```
fdpi_ctrl load profile --service 3 --profile.name a31 --profile.json '{
"url_list" : "http://mysite.ru/myfile.bin" , "redirect" :
"http://mysite.ru/block", "federal" : true }'
Autodetected fastdpi params : dev='em1', port=29000
connecting 5.200.43.18:29000 ...
=====
hvers=0x3, hcmd=16 : bad profile (name or parameters), error code ecode=4
ierr_code=1 (service can't have profile)
```

Profile deletion

Result processing ... a/b/c/d/e

- a - in total
- b - succeeded
- c - profile not found
- d - profile is being used (i.e. there are subscribers with specified service and corresponding profile)
- e - internal error (look through fastdpi_alert.log)

Example (profile deletion):

```
fdpi_ctrl del profile --service 4 --profile.name a41
Autodetected fastdpi params : dev='em1', port=29000
connecting 5.200.43.18:29000 ...
=====
-----
1/1/0/0/0
```

Example (profile deletion command repetition):

```
fdpi_ctrl del profile --service 4 --profile.name a41
Autodetected fastdpi params : dev='em1', port=29000
connecting 5.200.43.18:29000 ...
=====
-----
1/0/1/0/0
```