

Содержание

Outgoing traffic management via feedback 3

Outgoing traffic management via feedback

The inbound traffic control is not efficient for bandwidth saving. Indeed, these data were already received, and their omitting leads to repeated transmissions again and again. This creates additional load.

TCP protocol and some kinds of application UDP based protocols may adjust to specified limitations by congestion control mechanism. However, the outbound traffic control on the subscriber's channel may save additional 10% of the whole operator's load compared to an ordinary policing.

This method is effective for "query - reply" protocols. The reduction of the outbound traffic (query) reduces the inbound one (reply). Most of application protocols belong to this type.

Let us complete the previous example by the parameter `htb_inbound_bw`:

```
htb_inbound_bw=rate 9mbit ceil 10mbit
htb_inbound_root=rate 2mbit ceil 10mbit
htb_inbound_class0=rate 8bit ceil 10mbit
htb_inbound_class1=rate 1mbit ceil 3mbit
htb_inbound_class2=rate 8bit ceil 10mbit
htb_inbound_class3=rate 8bit ceil 10mbit
htb_inbound_class4=rate 8bit ceil 10mbit
htb_inbound_class5=rate 8bit ceil 10mbit
htb_inbound_class6=rate 8bit ceil 10mbit
htb_inbound_class7=rate 8bit ceil 10mbit
htb_root=rate 2mbit ceil 10mbit
htb_class0=rate 8bit ceil 10mbit
htb_class1=rate 1mbit ceil 3mbit
htb_class2=rate 8bit ceil 10mbit
htb_class3=rate 8bit ceil 10mbit
htb_class4=rate 8bit ceil 10mbit
htb_class5=rate 8bit ceil 10mbit
htb_class6=rate 8bit ceil 10mbit
htb_class7=rate 8bit ceil 10mbit
```

The inbound traffic limit and its maximum excess are indicated by the parameter `htb_inbound_bw`. The upper limit for the outbound traffic (parameter `htb_root` `ceil=10mbit`) is lowered to `htb_root` `rate=2mbit` upon the inbound traffic exceeds `rate=9mbit` specified in `htb_inbound_bw`. The excess traffic percentage is counted by the range `ceil 10mbit ↔ rate 9mbit`. The outbound traffic is reduced proportionally by the same percentage. Other classes redistribute the traffic according to their priorities and specified limitations upon reaching the `ceil` value specified in `htb_root` parameter. This allows not to exceed the general limit set up in `htb_root`.