

# Содержание

<b>2 How to troubleshoot the subscriber bandwidth allocation? .....</b>	<b>3</b>
---	----------



## 2 How to troubleshoot the subscriber bandwidth allocation?

The absence of bandwidth restrictions indicates there is a problem to solve.

Add the following option to the /etc/dpi/fastdpi.conf file:

```
plc_trace_ip=109.234.130.131
```

Reload fastdpi service:

```
service fastdpi reload
```

Reload the bandwidth constraints rules:

```
fdpi_ctrl load --policing rat_HTB.cfg --ip 109.234.130.131
```

Check all the fastdpi policing settings:

```
fdpi_ctrl list all --policing
```

```
Autodetected fastdpi params : dev='em3', port=29000  
connecting 217.74.168.149:29000 ...
```

```
109.234.130.131 HTB dnlnk_rate=0.00mbit dnlnk_ceil=0.00mbit  
rrate=500000(4.00mbit) rburst=250000(2.00mbit) rceil=500000(4.00mbit)  
rcburst=250000(2.00mbit) rate0=0.51mbit ceil0=3.00mbit rate1=0.01mbit  
ceil1=1.00mbit rate2=0.01mbit ceil2=1.00mbit rate3=0.01mbit  
ceil3=1.00mbit rate4=0.01mbit ceil4=1.00mbit rate5=0.01mbit  
ceil5=1.00mbit rate6=0.01mbit ceil6=1.00mbit rate7=0.01mbit  
ceil7=1.00mbit HTB_INBOUND rrate=250000(2.00mbit)  
rburst=125000(1.00mbit) rceil=375000(3.00mbit)  
rcburst=187500(1.50mbit) rate0=0.51mbit ceil0=2.00mbit rate1=0.01mbit  
ceil1=1.00mbit rate2=0.01mbit ceil2=1.00mbit rate3=0.01mbit  
ceil3=1.00mbit rate4=0.01mbit ceil4=1.00mbit rate5=0.01mbit  
ceil5=1.00mbit rate6=0.01mbit ceil6=1.00mbit rate7=0.01mbit ceil7=1.00mbit
```

The rules are loaded successfully.

Check the statistics log for the given IP. Not empty log indicates the presence of the traffic, otherwise it indicates that the traffic is not routed through the VAS Experts DPI or the interfaces are not configured properly(in\_dev should be oriented towards the subscribers). Let's analyse the stat.log (using the grep output) for the given IP:

```
grep -A 7 "109.234.130.131" /var/log/dpi/fastdpi_stat.log | more
```

The outgoing traffic:

```
[STAT    ][2014/10/30-19:25:16:441786] HTB : Statistics
(IP=109.234.130.131) dscp=7, if 'dna2' :
    DSCP_actual stats Rcvd: [358187060 bytes][47.73 Mbit/sec]
                        [232589 pkts ][3'874.07 pkt/sec]
    Drop: [354236960 bytes][98.90 %]
          [230024 pkts ][98.90 %]
    Send: [0 bytes][0.00 Mbit/sec]
          [0 pkts ][0.00 pkt/sec]
    Esnd: [0 err_pkts][0.00 %]
```

The incoming traffic > 0:

```
[STAT    ][2014/10/30-19:25:16:441793] HTB : Statistics
(IP=109.234.130.131) dscp=0, if 'dna3' :
    DSCP_actual stats Rcvd: [1018 bytes][0.00 Mbit/sec]
                        [10 pkts ][0.17 pkt/sec]
    Drop: [0 bytes][0.00 %]
          [0 pkts ][0.00 %]
    Send: [828 bytes][0.00 Mbit/sec]
          [9 pkts ][0.15 pkt/sec]
    Esnd: [0 err_pkts][0.00 %]
```

```
[STAT    ][2014/10/30-19:25:16:441834] HTB : Statistics
(IP=109.234.130.131) dscp=7, if 'dna3' :
    DSCP_actual stats Rcvd: [0 bytes][0.00 Mbit/sec]
                        [0 pkts ][0.00 pkt/sec]
    Drop: [0 bytes][0.00 %]
          [0 pkts ][0.00 %]
    Send: [3950100 bytes][0.53 Mbit/sec]
          [2565 pkts ][42.72 pkt/sec]
    Esnd: [0 err_pkts][0.00 %]
```

Therefore, the outgoing traffic is limited, it is indicated by the non zero Drop entries, so the incoming traffic is routed alternatively and does not fall under the rules loaded in the VAS Experts DPI.