

Содержание

Management	3
<i>Management of a default profile (service 5):</i>	3
<i>Management of a named profile (service 5):</i>	3
<i>Management of a named profile (service 16):</i>	4

Management

This service is configured for individual subscribers by `fdpi_ctrl`.

Instruction format:

```
fdpi_ctrl command --service 5 [Services_list] [IP_list]
```

The instruction syntax and IP addresses specification methods are described in details here: [Control instructions](#).

Management of a default profile (service 5):

1. Enable the "white list" operation for the particular subscriber with **a default profile** (is specified in `etc/dpi/fastdpi.conf` configuration file):

```
fdpi_ctrl load --service 5 --ip 192.168.0.1
```

2. Disable the "white list" operation for the particular subscriber:

```
fdpi_ctrl del --service 5 --ip 192.168.0.1
```

Management of a named profile (service 5):

1. In order to create **a named profile** and activate the locking service with a profile for several subscribers:

```
fdpi_ctrl load profile --service 5 --profile.name test_white --profile.json '{ "url_list" : "http://mysite.ru/myfile.bin" , "sni_list" : "http://mysite.ru/myfilesni.bin", "ip_list" : "http://mysite.ru/myfileip.bin", "cn_list" : "http://mysite.ru/myfilecn.bin", "redirect" : "mysite.ru/block" }'
```

here the following profile settings using the json format are specified:

- `redirect` — the redirection page¹⁾²⁾
- `url_list` — white URL list
- `sni_list` — white SNI list
- `ip_list` — white list of IP:PORT pairs³⁾
- `cn_list` — white list of Common Name⁴⁾



The list can be placed both on an external resource - in this case it is loaded before it is used, and in a local file, for example, `cn_list : /tmp/cn_list.bin`

2. Connection of blocking service with a profile for multiple subscribers:

```
fdpi_ctrl load --service 5 --profile.name test_white --ip 192.168.0.1
fdpi_ctrl load --service 5 --profile.name test_white --login user01
```

3. To search for subscribers who have an activated alert service with the specified profile name:

```
fdpi_ctrl list all --service 5 --profile.name test_white
```

4. To delete a named profile(there should be no subscribers using this profile):

```
fdpi_ctrl del profile --service 5 --profile.name test_white
```

5. Change of service (profile) settings (new settings are applied to all subscribers with the specified service profile):

```
fdpi_ctrl load profile --service 5 --profile.name test_white --profile.json
'{ "url_list" : "http://mysite.ru/newfile.bin" , "ip_list" :
"http://mysite.ru/myfileip.bin", "cn_list" :
"http://mysite.ru/myfilecn.bin", "redirect" : "mysite.ru/block" }'
```

Management of a named profile (service 16):

1. In order to create a **named profile** and activate the locking service with a profile for several subscribers:

```
fdpi_ctrl load profile --service 16 --profile.name portal_info_1 --profile.json
'{ «ip_list» : «/var/lib/dpi/ip_list_1.bin», «redirect» : «http://info.com»
}'
```

here the following profile settings using the json format are specified:

- `redirect` — the redirection page⁵⁾⁶⁾
- `ip_list` — white list of IP:PORT pairs⁷⁾

2. Connection of blocking service with a profile for multiple subscribers:

```
fdpi_ctrl load --service 16 --profile.name portal_info_1 --ip 192.168.0.1
fdpi_ctrl load --service 16 --profile.name portal_info_1 --login user01
```



When the service is activated, only TCP traffic is blocked. To block UDP traffic as well, you must [enable the `udp_block` parameter](#).

3. To search for subscribers who have an activated alert service with the specified profile name:

```
fdpi_ctrl list all --service 16 --profile.name portal_info_1
```

4. To delete a named profile(there should be no subscribers using this profile):

```
fdpi_ctrl del profile --service 16 --profile.name portal_info_1
```

5. Change of service (profile) settings (new settings are applied to all subscribers with the specified service profile):

```
fdpi_ctrl load profile --service 16 --profile.name portal_info_1 --profile.json  
'{ «ip_list» : «/var/lib/dpi/new_ip_list_1.bin», «redirect» :  
«http://new.info.com» }'
```

1) 5)
,

Attention: if you specify the https site, then you have to put the given domain on the list of SNI otherwise the domain will be blocked

2) 6)
,

Additional parameters can be added (according to HTTP rules) only after ? or &, they must be specified in the URL for whitelisting and here you need to think for DPI, otherwise DPI will assign /?

3) 4)
,

a check against the ip:port or cname is run if the request does not contain URL or SNI

7)

Check by IP:Port