

Содержание

| | |
|--|----------|
| Configuring Full NetFlow Export in IPFIX Format | 3 |
| <i>Export Template in IPFIX Format (Netflow v10) for IPv4 Protocol</i> | <i>3</i> |
| <i>Export Template in IPFIX Format (Netflow v10) for IPv6 Protocol</i> | <i>5</i> |

Configuring Full NetFlow Export in IPFIX Format

The `netflow_full_collector_type` parameter defines the export format for full NetFlow. Possible values:

- **0** - export in NetFlow5 format (default value).
- **1** - export IPFIX to a UDP collector.
- **2** - export IPFIX to a TCP collector.

The `netflow_tos_format` parameter defines the format of the TOS field data in IPFIX. Possible values:

- **0** - 3 bits are transmitted (default value).
- **1** - 6 bits are transmitted (full DSCP).

The `netflow_plc_stat` parameter defines the set of transmitted statistics data for dropped packets according to policing or drop rules. The parameter is a bitmask.

By default, the mask has the value **0x07** — statistics for dropped data of session + subscriber + virtual channel policing are transmitted.

! Affects the formation of the `DROPPED_BYTES` and `DROPPED_PACKETS` counters.

Values that make up the mask:

- **0xff** - any drop is transmitted
- **0** - do not count
- **1** - count for session policing
- **2** - count for subscriber policing
- **4** - count for virtual channel policing
- **8** - count when packets are dropped (drop) by protocol
- **16** - count in all other cases

The `ipfix_mtu_limit` parameter sets the maximum UDP packet size when sending IPFIX. By default, it equals the minimum MTU of the interfaces used for sending.



For receiving, processing, and storing IPFIX, it is recommended to use the [QoE Store software for statistics collection](#) and the [DPIUI2 Graphical Interface](#).

For collecting information in IPFIX format, any universal IPFIX collector that understands templates, or the [IPFIX Receiver](#) utility, is suitable.

Export Template in IPFIX Format (Netflow v10) for IPv4 Protocol

| Export Template for IPv4 | | | | | | |
|--------------------------|-------|-----------|-------|---------------------------------|---|-------------|
| № | Bytes | Data Type | IANA | Description | Notes | Used in QoS |
| 1 | 8 | int64 | 0 | OCTET_DELTA_COUNT | Analog in NetFlow v9 IN_BYTES | Used |
| 2 | 8 | int64 | 0 | PACKET_DELTA_COUNT | Analog in NetFlow v9 IN_PKTS | Used |
| 4 | 1 | int8 | 0 | PROTOCOL_IDENTIFIER | Analog in NetFlow v9 PROTOCOL | Used |
| 5 | 1 | int8 | 0 | IP_CLASS_OF_SERVICE | Analog in NetFlow v9 TOS | Used |
| 7 | 2 | int16 | 0 | SOURCE_TRANSPORT_PORT | Analog in NetFlow v9 L4_SRC_PORT | Used |
| 8 | 4 | int32 | 0 | SOURCE_IPV4_ADDRESS | Analog in NetFlow v9 IPV4_SRC_ADDR | Used |
| 11 | 2 | int16 | 0 | DESTINATION_TRANSPORT_PORT | Analog in NetFlow v9 L4_DST_PORT | Used |
| 12 | 4 | int32 | 0 | DESTINATION_IPV4_ADDRESS | Analog in NetFlow v9 IPV4_DST_ADDR | Used |
| 16 | 4 | int32 | 0 | BGP_SOURCE_AS_NUMBER | Analog in NetFlow v9 SRC_AS | Used |
| 17 | 4 | int32 | 0 | BGP_DESTINATION_AS_NUMBER | Analog in NetFlow v9 DST_AS | Used |
| 152 | 8 | int64 | 0 | FLOW_START_MILLISECOND | | Used |
| 153 | 8 | int64 | 0 | FLOW_END_MILLISECOND | | Used |
| 10 | 2 | int16 | 0 | INPUT_SNMP | Analog in NetFlow v9 IngressInterface | Used |
| 14 | 2 | int16 | 0 | OUTPUT_SNMP | Analog in NetFlow v9 EgressInterface | Used |
| 60 | 1 | int8 | 0 | IP_VERSION | Analog in NetFlow v9 IP_PROTOCOL_VERSION | Used |
| 2000 | 8 | int64 | 43823 | SESSION_ID | | Used |
| 2001 | - | string | 43823 | HTTP_HOST or CN_HTTPS | | Used |
| 2002 | 2 | int16 | 43823 | DPI_PROTOCOL | | Used |
| 2003 | - | string | 43823 | LOGIN | Analog in Radius User-Name | Used |
| 225 | 4 | int32 | 0 | POST_NAT_SOURCE_IPV4_ADDRESS | | Used |
| 227 | 2 | int16 | 0 | POST_NAPT_SOURCE_TRANSPORT_PORT | | Used |
| 2010 | 2 | int16 | 43823 | FRGMT_DELTA_PACKS | Delta of fragmented packets. | Used |
| 2011 | 2 | int16 | 43823 | REPEAT_DELTA_PACK | Delta of retransmissions. | Used |
| 2012 | 4 | int32 | 43823 | PACKET_DELIVER_TIME | Delay (RTT/2) in ms (RTT=round-trip time). | Used |
| 2016 | 2 | int16 | 43823 | BRIDGE_CHANNEL_NUM | Channel number (vchannel) or bridge. If vchannels are configured in DPI, the channel number will be transmitted, otherwise the bridge number. | Used |
| 6 | 2 | int16 | 0 | TCP_FLAGS | TCP control bits | Used |

| Export Template for IPv4 | | | | | | |
|--------------------------|-------|-------------|-------|-----------------|--|-----------------|
| No | Bytes | Data Type | IANA | Description | Notes | Used in QoEStor |
| 58 | 2 | int16 | 0 | SRC_VLAN | VLAN ID | Used |
| 59 | 2 | int16 | 0 | DST_VLAN | VLAN mail identifier | Used |
| 56 | 6 | mac_address | 0 | SRC_MAC | Source MAC address | Used |
| 57 | 6 | mac_address | 0 | DST_MAC | Destination MAC address | Used |
| 2017 | - | raw | 43823 | MPLS Lables | | Used |
| 132 | 8 | int64 | 0 | DROPPED_BYTES | Delta count of dropped octets. <i>For example: data is dumped at minute T1 and T2. The delta will show the difference in the number of octets between minute T1 and T2.</i> | Used |
| 133 | 8 | int64 | 0 | DROPPED_PACKETS | Delta count of dropped packets. <i>For example: data is dumped at minute T1 and T2. The delta will show the difference in the number of packets between minute T1 and T2.</i> | Used |
| 2019 | 1 | int8 | 43823 | originalTOS | Original TOS value from IP header | Used |

Export Template in IPFIX Format (Netflow v10) for IPv6 Protocol

The template is similar to IPv4 except that the following fields are absent: **SOURCE_IPV4_ADDRESS**, **DESTINATION_IPV4_ADDRESSES**, **POST_NAT_SOURCE_IPV4_ADDRESS**, **POST_NAT_SOURCE_TRANSPORT_PORT**, - and the following are present:

| Export Template for IPv6 | | | | | |
|--------------------------|-------|-----------|------|--------------------------|------------------------------------|
| No | Bytes | Data Type | IANA | Description | Notes |
| 27 | 16 | int128 | 0 | SOURCE_IPV6_ADDRESS | Analog in NetFlow v9 IPV6_SRC_ADDR |
| 28 | 16 | int128 | 0 | DESTINATION_IPV6_ADDRESS | Analog in NetFlow v9 IPV6_DST_ADDR |