

Содержание

- SWa Authorization Interface Settings 3
 - Section "fast-epdg.auth.swa" 3
 - Section "fast-epdg.auth.swa.<diameter-aaa-client-name-n>" 3

SWa Authorization Interface Settings

Section "fast-epdg.auth.swa"

Parameter	Description	Value
app_id	Application ID	swa
realm	Serviced realm	epc.mncYYY.mccXXX.3gppnetwork.org
host	Client hostname	epdg.epc.mncYYY.mccXXX.3gppnetwork.org
<diameter-aaa-client-name-1> {}	AAA Client #1 parameters	
<diameter-aaa-client-name-2> {}	AAA Client #2 parameters	
<diameter-aaa-client-name-n> {}	AAA Client #n parameters	

Template:

```
fast-epdg {  
  auth {  
    interface =  
    swa {  
      app_id =  
      realm =  
      host =  
      <server-name> {}  
    }  
  }  
}
```

Example:

```
fast-epdg {  
  auth {  
    interface = SWm  
    swa {  
      app_id = swa  
      realm = epc.mnc002.mcc250.3gppnetwork.org  
      host = epdg.epc.mnc002.mcc250.3gppnetwork.org  
      <server-name> {}  
    }  
  }  
}
```

Section "fast-epdg.auth.swa.<diameter-aaa-client-name-n>"

Parameter	Description	Value
local	AAA Server address:port	AAA.BBB.CCC.DDD:XXXX, [1111.2222.3333.4444.5555.6666.7777.8888]:XXXX
remote	AAA Client address:port	AAA.BBB.CCC.DDD:XXXX, [1111.2222.3333.4444.5555.6666.7777.8888]:XXXX
proto	Transport protocol	[sctp][tcp]

Template:

```
fast-epdg {
  auth {
    interface =
    swa {
      app_id =
      realm =
      host =
      diameter-aaa-client-1 {
        priority =
        local =
                                remote =
                                proto =
      }
      diameter-aaa-client-2 {
        priority =
        local =
                                remote =
                                proto =
      }
    }
  }
}
```

Template:

```
fast-epdg {
  auth {
    interface = SWm
    swa {
      app_id = swa
      realm = epc.mnc002.mcc250.3gppnetwork.org
      host = epdg.epc.mnc002.mcc250.3gppnetwork.org
      diameter-aaa-client-1 {
        priority =
        local = 192.168.1.1:3868
                                remote = 192.168.2.1:3868
                                proto = sctp
      }
      diameter-aaa-client-2 {
        priority =
        local = 192.168.1.1:3869
                                remote = 192.168.2.2:3868
      }
    }
  }
}
```

```
proto = tcp
```

```
}
```

```
}
```

```
}
```

```
}
```