

# Содержание

Interface configuration example .....	3
---------------------------------------	---



# Interface configuration example

The default configuration file is in `/etc/epdg/fast-epdg.conf`.  
The following is an example of interface configuration:



- SWu
- SWm
- SWx
- S6b
- GTP
- GTP-C
- GTP-U

In the example, the blocks corresponding to the interfaces are highlighted with a marker.

```
fast-epdg {
  swu {
    <config-name> {
      apn=
      leftsubnet=
    }
  }

  auth {
    iface =
    swm {
      realm =
      host =
      <server-name> {
        priority =
        local =
        remote =
        proto =
        tls =
      }
    }
  }
  swx {
    realm =
    host =
    <server-name> {
      priority =
      local =
      remote =
      proto =
      tls =
    }
  }
}
```

```

    }
s6b {
    realm =
    host =
    <server-name> {
        priority =
        local =
        remote =
        proto =
        tls =
    }
}

tunnel {
    iface =
    pdn =
pgw {
gtp {
    mcc =
    mnc =
    tac =
    cid =
    enbid =
    realm =
    <server-name> {
        apn =
        priority =
        devname =
        subnet =
gtp-c {
    local =
    remote =
}
gtp-u {
    local =
    remote =
}
}
}
}
}
}
}

syslog {
    daemon {
        cfg =
        lib =
    }
}
}

```