

Содержание

Interface configuration example	3
--	-------	---

Interface configuration example

The default configuration file is in `/etc/epdg/fast-epdg.conf`.

The following is an example of interface configuration:



- `SWu`
- `SWm`
- `SWx`
- `S6b`
- `GTP`
- `GTP-C`
- `GTP-U`

In the example, the blocks corresponding to the interfaces are highlighted with a marker.

```
fast-epdg {
    swu {
        <config-name> {
            apn=
            leftsubnet=
        }
    }

    auth {
        iface =
        swm {
            realm =
            host =
            <server-name> {
                priority =
                local =
                remote =
                proto =
                tls =
            }
        }
    }

    swx {
        realm =
        host =
        <server-name> {
            priority =
            local =
            remote =
            proto =
            tls =
        }
    }
}
```

```
        }
    s6b {
        realm =
        host =
        <server-name> {
            priority =
            local =
            remote =
            proto =
            tls =
        }
    }
}

tunnel {
    iface =
    pdn =
    pgw {
        gtp {
            mcc =
            mnc =
            tac =
            cid =
            enbid =
            realm =
            <server-name> {
                apn =
                priority =
                devname =
                devmode =
                subnet =
                qos {
                    qci =
                    mbr_ul =
                    mbr_dl =
                    gbr_ul =
                    gbr_dl =
                }
            }
            gtp-c {
                local =
                remote =
            }
            gtp-u {
                local =
                remote =
            }
        }
    }
}
```

```
syslog {  
    daemon {  
        cfg =  
        lib =  
    }  
}  
}
```