

Содержание

Interface configuration example	3
--	-------	---

Interface configuration example

The default configuration file is in /etc/epdg/fast-epdg.conf.

The following is an example of interface configuration:



- SWu
- SWm
- SWx
- S6b
- GTP
- GTP-C
- GTP-U

In the example, the blocks corresponding to the interfaces are highlighted with a marker.

```
fast-epdg {
    swu {
        <config-name> {
            apn=
            leftsubnet=
        }
    }

    auth {
        iface =
        swm {
            realm =
            host =
            <server-name> {
                priority =
                local =
                remote =
                proto =
            }
        }
        swx {
            realm =
            host =
            <server-name> {
                priority =
                local =
                remote =
                proto =
            }
        }
    }
    s6b {
```

```
realm =
host =
<server-name> {
    priority =
    local =
    remote =
    proto =
}
}

tunnel {
    iface =
    pdn =
pgw {
    gtp {
        mcc =
        mnc =
        tac =
        cid =
        enbid =
        realm =
        <server-name> {
            apn =
            priority =
            devname =
            devmode =
            subnet =
            qos {
                qci =
                mbr_ul =
                mbr_dl =
                gbr_ul =
                gbr_dl =
            }
        }
        gtp-c {
            local =
            remote =
        }
        gtp-u {
            local =
            remote =
        }
    }
}
}

syslog {
    daemon {
        cfg =

```

```
    lib =  
        }  
    }  
}
```