

Содержание

Description of NAT statistics	3
Common for all profiles	3
CG-NAT Profile	3
Information on the data converter	3
1:1 Profile	5
Output of public addresses statistics	5

Description of NAT statistics

The output of statistics in `fastdpi_stat.log` is set by `dbg_log_mask`.

0x40000 - output of NAT initialization details (profiles, public addresses, etc.) to the alert log

0x100000 - output of statistics by blocks of public addresses (if 0x2000000 is set)

0x2000000 - NAT statistics output.

Example:

```
dbg_log_mask=0x2000000
```

Common for all profiles

```
[STAT    ][2021/12/22-17:33:17:513859] NAT statistics : itrnsl=0, iprof=2,
profile 'cgnat', nttype=0, ref_cnt=1, cidr=94.140.198.84/30
[STAT    ][2021/12/22-17:33:17:513869] NAT statistics : itrnsl=1, iprof=3,
profile 'nat1_1', nttype=1, ref_cnt=1, cidr=16.35.121.0/24

itrnsl - internal index of the private<-->public proile converter.
iprof  - internal index of the profile
profile - profile name
nttype - profile type (0 - cgnat, 1 - 1:1)
ref_cnt - counter of references of converter usage by profiles
(Profiles can use one set of CIDR, but different number of restrictions
per session)
cidr   - list of profile's public addresses CIDR
```

CG-NAT Profile

```
[STAT    ][2021/12/22-17:33:19:252622] NAT statistics : itrnsl=0, iprof=2,
profile 'cgnat', nttype=0, ref_cnt=1, cidr=94.140.198.84/30
k=0, itrnsld=0, cidr=94.140.198.84/30
    total TCP : 30/20/0/7/17/ 0/0/0 50/20/0/50/0 5516/8/121
    actual TCP : 0/0/0/0/0 0/0/0 0/0/0/0/0 0/0/0
    total UDP : 13/4/0/13/1/ 0/0/0 17/4/11/17/0 28/1/3
    actual UDP : 0/0/0/0/0 0/0/0 0/0/0/0/0 0/0/0
    total GRE : 0/0
```

Information on the data converter

```
k=0, itrnsld=0, cidr=94.140.198.84/30
k          - itrnsld number
itrnsld   - internal converter data index - the one serving the CIDR
cidr      - exact cidr
```

```
total - total statistics
actual - статистика изменений счетчиков за период вывода статистики
(delta_alarm parameter, 15 seconds by default)
```

```
total TCP : 30/20/0/7/17 0/0/0 50/20/0/50/0 5516/8/121
```

Four groups группы:

1 group -- operations with public address ports

30/20/0/7/17:

```
30 - allocation of a new public port
20 - public port reuse
0 - errors of allocating a new public port
7 - performs decrement of number of subscriber sessions on flow releasing
17 - performs decrement of the number of subscriber sessions on public port reuse
```

2 group -- general statistics

0/0/0:

```
0 - calculated CRC by IP when accessed to allocate a public address. Should be == 0
0 - excessive number of sessions for subscribers
0 - different public addresses in flow and converters - Should be == 0
```

3 group -- cache statistics *private* --> *public*

50/20/0/50/0:

```
50 - added records to cache
20 - deleted records from cache
0 - found records in cache when new public port is allocated
50 - no public address found for private
0 - errors of adding to cache
```

4 group -- conversion statistics *public* --> *private* (*inet*-->*subs*)

5516/8/121:

```
5516 - successful translation public --> private
8 - port is not in the allocated range of public ports
121 - translation public --> private was not found
```

For TCP/UDP and total/actual statistics are the same.

For GRE - it is GRE by default (when session is not found in PPTP). Only one such session can be created per public address.

```
total GRE : 0/0
0 - address used
0 - number of attempts to create sessions on an already allocated public
address
```

1:1 Profile

```
[STAT    ][2021/12/22-17:17:28:749622] NAT statistics : itrnsl=1, iprof=3,
profile 'nat1_1', nttype=1, ref_cnt=1, cidr=16.35.121.0/24
      k=0, itrnsld=1, cidr=16.35.121.0/24
      total 256/256/0/0/0/0 0/0
```

Group 2 statistics:

1 group - 256/256/0/0/0/0

2 group - 0/0

Example:

dbg_log_mask=0x2100000

Output of public addresses statistics

```
[STAT    ][2021/12/22-21:14:48:385991] NAT statistics : itrnsl=0, iprof=2,
profile 'cgnat', nttype=0, ref_cnt=1, cidr=94.140.198.84/30
      k=0, itrnsld=0, cidr=94.140.198.84/30
      total TCP : 26/4/0/4/2/ 0/0/0 30/4/0/30/0 3045/1/36
      actual TCP : 0/0/0/0/0 0/0/0 0/0/0/0/0 0/0/0
      TCP whiteblk ip_mask=0x0, nwhaddr=2
      whip=94.140.198.84 : sb=64, lsb=64, nb=1008,
whpa=64512, whpb=0, whpf=64512, awhb=4, fwhb=1004, puwhb=0.40%
      thr=0, ublock=1, uport=0
      thr=1, ublock=1, uport=0
      thr=2, ublock=1, uport=0
      thr=3, ublock=1, uport=0
      whip=94.140.198.86 : sb=64, lsb=64, nb=1008,
whpa=64512, whpb=26, whpf=64486, awhb=4, fwhb=1004, puwhb=0.40%
      thr=0, ublock=1, uport=0
      thr=1, ublock=1, uport=0
      thr=2, ublock=1, uport=13
      thr=3, ublock=1, uport=13
```

TCP whiteblk ip_mask=0x0, nwhaddr=2 :

ip_mask - addresses mask

nwhaddr - the number of public addresses that are under the mask

```
whip=94.140.198.84 : sb=64 ( 64 ), nb=1008, whpa=64512, whpb=0, whpf=64512,
awhb=4, fwhb=1004, puwhb=0.40%
```

```
whip=94.140.198.84 - public address
sb=64             - port block size
lsb=64           - size of the last block
nb=1008          - number of port blocks
whpa=64512       - total ports
whpb=0           - ports occupied
whpf=64512       - free ports
awhb=4          - blocks issued
fwhb=1004        - free blocks
puwhb=0.40%     - percentage of blocks occupied
```

Added in version 12.1.0

```
whp_salfs        - how many ports are in the 'short' queue
whp_lalfs        - how many ports are in the 'long' queue
whp_ruse         - how many ports can be reused
whp_ruse_salfs   - how many ports can be reused from the 'short' queue
whp_ruse_lalfs   - how many ports can be reused from the 'long' queue
whp_dthr         - how many ports were created in one worker thread but used in
another thread
whp_dthr_salfs   - how many ports were created in one worker thread but used
in another from the 'short' queue
whp_dthr_lalfs   - how many ports were created in one worker thread but used
in another from the 'long' queue
```

Within the public address you can see the distribution of captured ports/blocks by worker threads

```
thr=0, ublock=1, uport=0
thr=0 - worker thread number
ublock=1 - public ports blocks used
uport=0 - public ports used
```

```
thr_salfs        - how many ports are in the 'short' queue
thr_lalfs        - how many ports are in the 'long' queue
thr_ruse         - how many ports can be reused
thr_ruse_salfs   - how many ports can be reused from the 'short' queue
thr_ruse_lalfs   - how many ports can be reused from the 'long' queue
thr_dthr         - how many ports were created in one worker thread but used in
another thread
thr_dthr_salfs   - how many ports were created in one worker thread but used
in another from the 'short' queue
thr_dthr_lalfs   - how many ports were created in one worker thread but used
in another from 'long' queue
```

The output format is the same.

```
fdpi_ctrl list status --service 11 --ip 192.168.4.20
Autodetected fastdpi params : dev='em1', port=29001
connecting 94.140.198.68:29001 ...
```

```
=====
192.168.4.20    crcip=0xd649d853      ntttype=0      profile='cgnat'
itrnsl=0 itrnsl=0      whiteip=94.140.198.86  sess_tcp=127
active_sess_tcp=0      sess_udp=108      active_sess_udp=1      indmtd=4
```

Output:

```
192.168.4.20      - private IP
crcip=0xd649d853  - CRC of the private IP
ntttype=0         - NAT type: 0 - cgnat, 1 - 1:1
profile='cgnat'   - profile name
itrnsl=0          - internal index of the converter private<-->public profile.
itrnsl=0          - internal converter data index
whiteip=94.140.198.86 - public address
sess_tcp=127      - number of TCP sessions
active_sess_tcp=0 - Number of active NAT translations for TCP
sess_udp=108      - number of UDP sessions
active_sess_udp=1 - Number of active NAT translations for UDP
indmtd=4          - internal index of subscriber data (subscriber
metadata)
```

```
fdpi_ctrl list status --service 11 --ip 192.168.4.20 --outformat=json
fdpi_ctrl list status --service 11 --ip 192.168.4.20 --outformat=json | jq
.
```

```
fdpi_ctrl list all status --service 11
fdpi_ctrl list all status --service 11 --outformat=json
```

The format is the same.

Key to command to view NAT profile statistics via fdpi_ctrl

Command:

```
fdpi_ctrl list status --service 11 --profile.name cgnat
```

Output:

```
ntttype=0      profile='test_nat_cgnat'      itrnsl=0      nitrnsl=1
      itrnsl=0      cidr=94.140.198.84/30
      proto=TCP      ip_mask=0x0      nwhaddr=2
      proto=TCP      ip_mask=0x0      whip=94.140.198.84
sb=64  lsb=64  nb=1008  whpa=64512      whpb=0  whpf=64512      awhb=4
fwhb=1004      puwhb=0.40%      whp_salfs=0      whp_lalfs=0      whp_ruse=0
whp_ruse_salfs=0      whp_ruse_lalfs=0      whp_dthr=0
whp_dthr_salfs=0      whp_dthr_lalfs=0
      nthr=0  ublock=1      uport=0  thr_salfs=0
thr_lalfs=0      thr_ruse=0      thr_ruse_salfs=0      thr_ruse_lalfs=0
thr_dthr=0      thr_dthr_salfs=0      thr_dthr_lalfs=0
```

```

nthr=1  ublock=1      uport=0 thr_salfs=0
thr_lalfs=0  thr_ruse=0      thr_ruse_salfs=0    thr_ruse_lalfs=0
thr_dthr=0   thr_dthr_salfs=0  thr_dthr_lalfs=0

```

Key:

```

nttype      - profile type (0 - cgnat, 1 - 1:1)
profile     - profile name
itrnsl      - internal index of private<-->public profile converter
nitrnsld    - number of profile converter data (number of CIDR)
itrnsld     - internal converter data index - the one serving the CIDR
cidr        - exact CIDR
proto       - TCP/UDP
ip_mask     - addresses mask
nwaddr      - the number of public addresses which fall under the mask or
CRC (depends on rx_dispatcher parameter)
whip        - public address
sb          - size of the block of ports to be allocated
lsb         - size of the last block
nb          - number of prot blocks
whpa        - ports in total
whpb        - ports occupied
whpf        - free ports
awhb        - blocks issued
fwhb        - free blocks
puwhb       - percentage of blocks occupied
whp_salfs   - is in the 'short' queue
whp_lalfs   - in the 'long' queue
whp_ruse    - can be used
whp_ruse_salfs - can be used in 'short' queue
whp_ruse_lalfs - can be used in 'long' queue
whp_dthr    - number of elements ithr_owner != ithr by queue
whp_dthr_salfs - number of elements ithr_owner != ithr by 'short' queue
whp_dthr_lalfs - number of elements ithr_owner != ithr by 'long' queue

```



rx_dispatcher parameter description [at the link](#)

Key to command to view the dump NAT profile statistics

Command:

```
fdpi_cli nat dump whaddr queue test_nat_cgnat
```

Output:

```

profile='test_nat_cgnat' itrnsl=0
      cidr='94.140.198.84/30' itrnsld=0

```

```

        whip=94.140.198.86
          proto=TCP
            entryp :
              ithr=0, ihead=0, itail=0
              ithr=1, ihead=0, itail=0
              ithr=2, ihead=133, itail=265
              ithr=3, ihead=193, itail=327
            data :
              sind=129, inext=257, iprev=258,
whport=1152, graddr=192.168.4.20:60637 tml='2023/03/06 16:28:09,
-00:00:10.657 (7472516905147512 ticks)', lifetime=120, canreuse=0, ialf=1,
imtd=516, iown=2, ilst=2, subproto=0, decr_sess=0, ind_gcache_slice=1,
igcache=40
              sind=130, inext=151, iprev=148,
whport=1153, graddr=192.168.4.20:52553 tml='2023/03/06 16:27:50,
-00:00:29.455 (7472459405058624 ticks)', lifetime=30, canreuse=0, ialf=0,
imtd=516, iown=2, ilst=2, subproto=0, decr_sess=0, ind_gcache_slice=1,
igcache=1

```

Key:

```

profile      - profile name
itrnsl       - internal index of the private<-->public profile converter

cidr         - exact CIDR
itrnslld     - internal converter data index - the one serving the CIDR

whip         - public address
proto        - TCP/UDP

```

The implementation of the used ports queue for public addresses uses a single array - let's call it WHP, of size 0xffff. It is used to build a list of used ports for the worker thread. Index 0 is used as a stub (empty).

Thread queues cannot be output as a list, because records in the queue are moved in the process, which may cause the output to loop. Therefore, the WHP array is output 'as is' for occupied entries.

```

entryp : sets entry points to the list of public ports of the worker thread
  ithr   - worker thread number
  ihead  - top of the list
  itail  - the last element of the list

```

```

data : WHP white port array data (only occupied entries are output)

```

```

  sind      - record index
  inext     - next record index
  iprev     - previous record index
  whport    - public port
  graddr    - private address, which the public address is assigned
to
  tml      - time of the last record access

```

```

lifetime      - timeout, time in seconds, the record lifetime
(depends on the parameters for short/long queue)
  canreuse    - sign that the record can be used again
  ialf        - number of the processing queue :
                en_nalfs_shrt = 0, # queue with a short
lifetime
                en_nalfs_long = 1, # long queue
  indmtd      - internal index of the subscriber's data (subscriber's
metadata)
  iown        - owner thread which has created the record
  ilst        - number of the thread which has last accessed the
record
  subproto    - the protocol the record was allocated for from UDP
                typedef enum en_nat_borrw_udp: u_int8_t
                {
                    ennatborwu_ORG      = 0, # UDP/TCP
                    ennatborwu_DFLTGRE   = 1, # общий GRE
                    ennatborwu_MAX      = 2, # ICMP
                } en_nat_borrw_udp_t;
  decr_sess   - a mark that the port usage counter on the private
address has decremented
  ind_gcache_slice - index of the 'private --> public' transcoding cache-
slice
  igcache     - index in the corresponding cache-slice recoding
'private --> public'

```