

Содержание

In order to filter a traffic of some particular subscribers, or exclude filtering of transit traffic, or provide filtering to other operators as a service - you will need to activate Subscriber Management to control this service. Please add configuration parameter to the file `/etc/dpi/fastdpi.conf` to activate:

```
black_list_sm=1
```

As a result, this service is configured on level of individual subscribers by [fdpi_ctrl](#).

Instruction format:

```
fdpi_ctrl command --service 4 [IP_list]
```

You can find more details on the instruction syntax and IP specification methods here: [Control instructions](#)

Examples:

Activate the service for all subscribers and switch filtering off for an administrator:

```
fdpi_ctrl load --service 4 --cidr 192.168.0.0/24
fdpi_ctrl del --service 4 --ip 192.168.0.1
```

Enable the service for an independent system AS50538:

```
fdpi_ctrl load --service 4 --cidr 37.110.240.0/21 --cidr 109.235.216.0/21
```

Creating named profile and activating it to several subscribers

```
fdpi_ctrl load profile --service 4 --profile.name test_black --profile.json
'{ "url_list" : "http://mysite.ru/myfile.bin" , "ip_list" :
"http://mysite.ru/myfileip.bin", "cn_list" :
"http://mysite.ru/myfilecn.bin", "redirect" : "http://mysite.ru/block",
"federal" : 0 }'
fdpi_ctrl load --service 4 --profile_name test_black --ip 192.168.0.1
fdpi_ctrl load --service 4 --profile_name test_black --ip 192.168.0.2
```

here

in json format sets following profiles' parameters

redirect - web page to redirect to

federal : 0/1/2/etc. using local authorities blacklist

url_list - URL blacklist

ip_list - IP:PORT blacklist

cn_list - Common Name blacklist

Blacklist can be loaded from external source, like "<http://mysite.ru/myfilecn.bin>", or in a local file, like
"cn_list" : `"/tmp/cn_list.bin"`

Searching subscribers with named profile:

```
fdpi_ctrl list all --service 4 --profile.name test_black
```

Deleting subscribers with named profile (the named profile has no subscribers using it)

```
fdpi_ctrl del profile --service 4 --profile.name test_black
```

Changing parameters of named profile (new settings apply to all subscribers with the named profile)

```
fdpi_ctrl load profile --service 4 --profile.name test_black --profile.json  
'{ "url_list" : "http://mysite.ru/myfile.bin" , "ip_list" :  
"http://mysite.ru/myfileip.bin", "cn_list" :  
"http://mysite.ru/myfilecn.bin", "redirect" : "http://mysite.ru/block",  
"federal" : false }'
```

Maximum number of profiles for blacklist service is configured by a parameter in /etc/dpi/fastdpi.conf

```
max_profiles_black_list=64
```

here

64 default value, 65535 maximum value the parameter is applied after service restart.