

Содержание

The system allows to record the traffic for selected protocols in PCAP format. It can save metadata of HTTP requests in log files.

To record the data in PCAP format: please use the following parameters in configuration file `/etc/dpi/fastdpi.conf`:

```
ajb_save_udpi=1
ajb_save_udpi_proto=OSPF:IGP:ospf-lite
ajb_udpi_path=/var/dump/dpi
ajb_save_ip=192.168.0.0/24
```

Here: `ajb_save_udpi=1` - activate the traffic recording for a list of protocols
`ajb_udpi_path=/var/dump/dpi` - is a directory to place log files (`/var/dump/dpi` by default)
`ajb_save_udpi_proto=OSPF:IGP:ospf-lite` - is a list of protocols to record [as test or numerical identifiers](#), . This is a hot parameter. It can be changed on the run by instruction **service fastdpi reload**
`ajb_save_ip=192.168.0.0/24` - activate the traffic recording by IP or CIDR (0.0.0.0/0 - to record all the traffic)

To record HTTP requests' metadata: please use the following parameters in configuration file `/etc/dpi/fastdpi.conf`:

```
ajb_save_url=-1
ajb_save_url_format=ts:prg:login:ipsrc:ipdst:host:path:ref:uagent:cookie
ajb_url_path=/var/dump/dpi
```

Here:

`ajb_save_url=-1` - activate recording of HTTP metadata
`ajb_url_path=/var/dump/dpi` - is the directory to place files with these records (`/var/dump/dpi` by default)
`ajb_save_url_format=ts:prg:login:ipsrc:ipdst:host:path:ref:uagent:cookie` - is the list of metadata to record:

```
ts - is a time stamp
prg - is: id of the active services at the moment of request
login - subscriber's login
ipsrc - subscriber's IP address
ipdst - host IP address (that of the request's addressee)
host - the host name (Host field)
path - the path to the requested resource (URI)
ref - from where (Referee field)
uagent - browser's type (User-Agent field)
cookie - Cookie
```

If you set the configuration parameter

```
ajb_reserved=1
```

the memory for a buffer is allocated in advance (on DPI start) and you can start and stop data recording on the run. You only need to change parameters `ajb_save_url`, `ajb_save_udpi` and

ajb_save_ip.