

Содержание

For all parameters except of list

Result processing ... a/b/c/d/e

```
The symbolic names are indicated in parenthesis:  
a - total records  
b - records successfully processed  
c - some server's error occurred  
d - the attribute(s) was set already  
e - the attribute was not set (meaningful on removal)
```

Example (the first run):

```
fdpi_ctrl load --service 1,2,3 --cidr 192.168.0.0/19  
Autodetected fastdpi params : dev='lo', port=29001  
connecting 127.0.0.1:29001 ...  
-----  
Result processing CIDR=192.168.0.0/19 : 8192/8192/0/0/0
```

Example (the second run: the attribute already set):

```
fdpi_ctrl load --service 1,2,3 --cidr 192.168.0.0/19  
Autodetected fastdpi params : dev='lo', port=29001  
connecting 127.0.0.1:29001 ...  
-----  
Result processing CIDR=192.168.0.0/19 : 8192/0/0/8192/0
```

For 'list' parameter

Result processing ... a/b/c

```
The symbolic names are indicated in parenthesis:  
a - total records  
b - the attribute was set (in this case it is a service)  
c - the attribute was not set
```

Example:

```
fdpi_ctrl list --service --cidr 192.168.0.0/19  
A lot of output lines. The last lines are:  
192.168.31.249 1,2,3 (0x7)  
192.168.31.250 1,2,3 (0x7)  
192.168.31.251 1,2,3 (0x7)  
192.168.31.252 1,2,3 (0x7)  
192.168.31.253 1,2,3 (0x7)  
192.168.31.254 1,2,3 (0x7)  
192.168.31.255 1,2,3 (0x7)  
-----  
Result processing CIDR=192.168.0.0/19 : 8192/8192/0
```